

Online Twisted Pair HD-TVI/HDCVI/AHD Surge Protection Device

ITEM NO.: SP009T HD-TVI /HDCVI /AHD Surge Protector




Application for protects equipment from high voltage surges such as lightning strikes. UL grounding requirements for coaxial cable offer protection from hazardous voltages that may occur on the shielding. Because of the physical length of ground wires, UL grounding systems may appear as an open circuit to lightning caused, high frequency surges and provide no protection from these surges getting into a home and destroying CATV converters, TV sets, VCR, Camera etc

SP009T UTP HD-TVI /HDCVI /AHD Surge Protector

- Terminal to terminal connector.
- Provide protection for analog/HD-CVI/HD-TVI/AHD camera and DVR devices.
- Comply with IEC 61000-4-5.
- Built in EFT (impulse noise), lightning protection.

Installation View



Application

- CATV System
- Antenna of Television
- Video Cassette Recorders
- FM receivers
- HD-TVI /HDCVI /AHD Cameras and DVR/Monitors

Recommend Cable

Link cable recommend to use high quality UTP CAT5/CAT5e/CAT6 cable, to use low quality coaxial cable may case signal loss and effect transmission distance and reliability.

Specification

ITEM NO	SP009T
Input and output interface	Terminal connector
Surge Protection Attack Time	< 1nS
Starting voltage surge	7V
Minimum Breakdown Voltage	6V
Maximum Clamping Voltage	25 V
Reference Standard	IEC 61000-4-5
Signal insertion loss	0.8db @ 42MHz
Maximum discharge current	15 KA (MAX)
Environmental Specifications	operation: 0 to 55°C, Storage: -20 to 85°C, Humidity: up to 95%
Dimensions	79.3x25.4x25.4 mm
Weight	75 g

RoHS CE FC

Rev.A

Distributed by:



53 Crownwood Road, Ormonde, Johannesburg, Gauteng,
Tel: +2711 496 2300, 0861 FRANK, Fax:+2711 496 2610,
Email: sales@frankstreet.co.za, www.frankstreet.co.za